

For information about other American International automotive accessories visit our website at:

<http://www.americaninternational.net>



**American
International**
Car Stereo Installation Kits & Accessories



GMK315 Mounting Kit



American International

Automotive Products Division

1040 Avenida Acaso • Camarillo, CA 93012, U.S.A.

USA Sales (800) 336-6500

Canada Sales (888) 922-3006 • USA Fax (805) 388-7950

CUSTOMER HELP LINE

USA 800-323-4329 • Canada 800-245-8777

iGMK315

VEHICLE APPLICATIONS

CHEVROLET

2012-13 SONIC

DASH DISASSEMBLY AND RADIO REMOVAL

1. With a soft tool remove OEM dash panel surrounding the radio, including air vents.
Note: if panel seems difficult to remove you can remove the glove box and push on the bottom right tab on the panel to help loosen.
2. Remove (4) 7mm Hex Head Screw. Remove radio and unplug all harnesses and antenna connections.
3. Remove OEM air vents to be used on the GMK315 panel.

KIT ASSEMBLY INSTRUCTIONS

Single ISO Mount Applications

Note: This kit is an (ISO) mounting kit only. The mounting sleeve of your new radio cannot be used when ISO mounting an aftermarket radio.

DO NOT attach the (4) OEM Panel metal clips yet.

1. Insert pocket into lower section of GMK315 panel, it will lock into place.
2. Insert ISO mountable radio between ISO mount brackets and loosely attach to sides of radio using screws provided with radio when possible, or screws supplied with kit.
3. Slide radio forward or backward for desired look and tighten screws.
4. You may use the trim ring supplied with you radio or the single din trim included with the GMK315.
5. Test fit kit/radio by mounting it using the (4) OEM screws, and making sure the main frame of the GMK315 aligns correctly and does not leave any gaps when installed. If everything looks correct go to step #6. If not, go back to step # 3.
6. Snap OEM air vents from OEM panel into the GMK315 panel.
7. Attach the metal panel fastener clips (from OEM panel) (4) to the mounting tab on the back side of the GMK315 panel.
8. Suggested...Attach a rear support bracket to the rear of the new radio and adjust as necessary to support the weight of the radio.

Fig A



Double DIN Mount Applications

DO NOT attach the (4) OEM Panel metal clips yet.

1. Insert ISO mountable radio between ISO mount brackets and loosely attach to sides of radio using screws provided with radio when possible, or screws supplied with kit.
2. Slide radio forward or backward for desired look and tighten screws.
3. You may use the trim ring supplied with you radio or the single din trim included with the GMK315
4. Test fit kit/radio by mounting it using the (4) OEM screws, and making sure the main frame of the GMK315 aligns correctly and does not leave any gaps when installed. If everything looks correct go to step #5. If not, go back to step # 2.
5. Snap OEM air vents from OEM panel into the GMK315 panel.
6. Attach the metal panel fastener clips (from OEM panel) (4) to the mounting tab on the back side of the GMK315 panel.
7. Suggested...Attach a rear support bracket to the rear of the new radio and adjust as necessary to support the weight of the radio.

Fig B

