For information about other American International automotive accessories visit our website at:

http://www.aius.net







WWW.AIUS.NET 2500 East Francis Street Ontario, CA 91761, U.S.A. USA Sales (800) 336-6500 Canada Sales (888) 922-3006

VEHICLE APPLICATIONS

Saturn 1995-99 S SERIES

CUSTOMER HELP LINE USA 800-323-4329 • Canada 800-245-8777

IGMK411

1995-99 Saturn S SERIES

DASH DISASSEMBLY INSTRUCTIONS

- 1. Carefully unclip and pull forward the radio dash trim bezel.
- 2. Unplug the hazard harness and remove trim bezel.
- 3. Remove the (2) 9/32 screws securing the factory radio to the sub-dash.
- 4. Pull radio forward, disconnect the wire harness and antenna lead and remove radio.

KIT INSTRUCTIONS

FOR ALL RADIOS

Remove rear pockets supports (left & right) from the center if the main frame and attach to the rear of the pocket.

DIN RADIOS

- 1. SUGGESTED...Attach rear support bracket to back of radio chassis using hardware supplied with radio (not supplied with kit).
- 2. Breakaway shaft radio mounting provisions in GMK411, main bracket .
- **NOTE:** Use wire cutter or the dull side of a razor knife, cut gradually along score lines of breakaway points, This will leave a rectangular opening in main bracket approx. 2 1/8" x 7 3/16" to mount your sleeve style radio. Using hardware supplied with the radio, install as per your radio's manufacturer's instructions.

STANDARD SHAFT TYPE RADIOS

1. Slide shaft spacers or threaded shaft nuts (supplied with radio) into radio shafts to adjust a flush protrusion of radio to face of kit. Slide unit into shaft openings of main bracket GMK411.

NOTES